

## Residential

# AIR TO WATER

- W-002 AIR TO WATER Overview
- W-004 Things We can Contribute to
- W-006 Energy Efficiency Standards
- W-008 AIR TO WATER Series Overview
- W-010 AIR TO WATER Lineup
- W-012 Monobloc Type
  - Comfort series
- W-022 Split Type
  - Comfort series
  - High Power series
  - Super High Power series
- W-038 Indoor Unit
  - Type-A, Type-B
- W-042 Optional Parts & Control Overview
- W-044 Optional Parts List for Type-A
- W-050 Control Overview
- W-052 Optional Parts Overview
- W-054 Optional Parts List for Type-B



AIR TO WATER  
Residential

# AIR TO WATER Overview

## Solutions That Meet a Variety of Needs


Water heated by Air to Water, which uses clean energy, can provide a steady supply of comfortable water throughout the home for heating and hot water applications.



## Air to water Heat Pump

### Outdoor unit

The unit is used to extract heat from the environment, making use of renewable energy resources from the sun and the outside air.



### Indoor unit control box\*

If you want to update your system by reusing your existing pump and buffer tank, etc., you can do so by installing only the control box.

OR



### Indoor unit Wall-mounted

Stands for preparation of heating water for under floor heating and radiators. It can optionally operate with domestic hot water tank.

OR



### Indoor unit Domestic Hot Water integrated


Can be used with a variety of heating systems, including under floor heating and radiators. Space saving heating and DHW supply in a single indoor unit.

\*The control box can only be selected for Monobloc outdoor unit.

## Ecological Consideration in Your Home

### Heat pump system framework

Heat is absorbed from the atmosphere by expanding the refrigerant. Higher-temperature heat is generated by compressing the refrigerant, and the indoor unit transfers that heat to the water.



\*Split products are listed as examples.

# Things We can Contribute to




## Our Goal

### Decarbonisation

European Commission is committed to decarbonisation and has a national target of “Net Zero” carbon emissions by 2050.


We need to reduce carbon emissions with green technology products and increase carbon absorption by working to extend nature.



General's ATW system will provide the best solutions that are friendly to the environment and people with products conscious of decarbonisation.

### What is a heat pump?


A heat pump extracts heat energy from the atmosphere. It requires only 1 kW of electricity to generate 3 to 5 kW of thermal energy.



### Primary energy usage reduced substantially

Proportion of primary energy converted into heating energy is 100%

#### Primary Energy Consumption\*




\* The amount of electricity loss varies according to the power plant. Typical energy efficiency of a power plant: 36%


## The Choice of Air to water

### Optimized refrigerant cycle operation


#### Split Type



#### Monobloc Type



# Energy Efficiency Standards Product Labels



Due to restrictions on the use of fossil fuels in Europe and the F-Gas regulations, the use of environmentally friendly heating equipment is required not only for new buildings but also for renovated properties. Let's consider installing high energy efficiency products that will be essential for future living environments.

## Heating Equipment



### The Ecodesign Directive Lot 1 Regulation 813/2013

The Ecodesign directive defines a regulatory framework for improving the environmental performance of energy-related products (ErP) through design. Since September 26, 2015, the Ecodesign Directive has applied to space heaters, including heat pumps and fossil fuel fired boilers, combination heaters for space and hot water heating, water heaters, and water storage tanks. All of these products must meet minimum requirements for energy efficiency\*1 and maximum sound power level. The minimum energy efficiency class were raised on September 26, 2017, and the maximum sound levels were lowered on September 26, 2018.

\*1: Energy efficiency is expressed in terms of seasonal space heating efficiencies ( $\eta_s$ ). The value is based upon the Seasonal Coefficient of Performance (SCOP).

### The Energy Labelling Directive (EU) No. 811/2013


Energy label is intended to enable consumers to make direct comparisons of energy use and product features. All labels should indicate the product identifier, efficiency class, sound power level, and heat output. Heat generators are rated A+++ to G. There are two different product labels. One for space heaters and one for combination heaters.

Seasonal space heating Energy efficiency class	
Except low temp. HP 55°C	Low temp. HP 35°C
<b>A+++</b> $\eta_s \geq 150$	$\eta_s \geq 175$
<b>A++</b> $125 \leq \eta_s < 150$	$150 \leq \eta_s < 175$
<b>A+</b> $98 \leq \eta_s < 125$	$123 \leq \eta_s < 150$
<b>A</b> $90 \leq \eta_s < 98$	$115 \leq \eta_s < 123$
<b>B</b> $82 \leq \eta_s < 90$	$107 \leq \eta_s < 115$
<b>C</b> $75 \leq \eta_s < 82$	$100 \leq \eta_s < 107$
<b>D</b> $36 \leq \eta_s < 75$	$61 \leq \eta_s < 100$
<b>E</b> $34 \leq \eta_s < 36$	$59 \leq \eta_s < 61$
<b>F</b> $30 \leq \eta_s < 34$	$55 \leq \eta_s < 59$
<b>G</b> $\eta_s < 30$	$\eta_s < 55$

# AIR TO WATER Series Overview

## ATW Product Simplified Selection Method

Please select a product based on the amount of heat required to maintain a comfortable temperature in the house, just as with air conditioners. For example, the Split comfort series with a low Capacity Range is recommended for newly built houses, as they tend to have high thermal insulation performance.



## RESIDENTIAL

### Monobloc type

Series	System Outline	Refrigerant	Recommended Buildings for Installation
<b>Comfort series</b> 	<b>Indoor unit</b> Control box consists of the hot water circuit controller and the user interface. It is not connected to the water pipe. <b>Outdoor unit</b> <ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -5°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Can be used with a variety of heating systems, including under floor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to Three independent control circuits.*</li> <li>Operating range is -20 to 35°C in heating.</li> <li>Cooling operation is possible</li> </ul>		 

\* Please refer to page W-042 to W-045 for optional parts information.










## RESIDENTIAL

### Split type

Series	System Outline	Refrigerant	Recommended Buildings for Installation
<b>Comfort series</b> 	<ul style="list-style-type: none"> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Heating and DHW supply in one system.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -20 to 35°C.</li> <li>Can be used with a variety of heating systems, including under floor heating and radiators.*</li> </ul>		
<b>NEW High power series</b> 	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -15°C.</li> <li>Can be used with a variety of heating systems, including under floor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to Two independent control circuits.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		 
<b>High power series</b> 	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Can be used with a variety of heating systems, including under floor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to two independent control circuits.*</li> <li>Cascade connection is possible for up to three systems.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		 
<b>Super high power series</b> 	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Can be used with a variety of heating systems, including under floor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		

\* Please refer to page W-050 to W-055 for optional parts information. For options for the R32 High Power Series, refer to W-042 through W-045.

# AIR TO WATER Lineup

Type	Series	Refrigerant	Model	Power Source	Capacity							Approval			
					5kw	6kw	8kw	10kw	11kw	14kw	16kw	17kw	CEN KEYMARK	EHPA	
Monobloc type	Comfort series Control box type	 Heating & Cooling		Single phase, ~230 V, 50 Hz	UTW-SCBHC WPHG050KRF			UTW-SCBHC WPHG080KRF	UTW-SCBHC WPHG100KRF						
	Comfort series Wall-mounted type	 Heating & Cooling		Single phase, ~230 V, 50 Hz	WSHP100KR3 WPHG050KRF			WSHP100KR3 WPHG080KRF	WSHP100KR3 WPHG100KRF						
	Comfort series DHW Integrated type	 Heating & Cooling		Single phase, ~230 V, 50 Hz	WGHP100KR3-19 WPHG050KRF			WGHP100KR3-19 WPHG080KRF	WGHP100KR3-19 WPHG100KRF						

\*Cooling is available by using the option



### SG ready Label



SG ready is a label issued to heat pumps and their control technologies that meet the requirements set by BWP<sup>4</sup>, and technologies that conform to their standards can be integrated into a smart grid. SG ready labeled heat pumps receive signals from the power grid and PV systems with regard to energy and renewable energy sources such as wind, solar, and water. All of General's heat pump series are SG ready compatible.

<sup>4</sup>: BWP: Bundesverband Wärmepumpe e. V (Federal German Heat Pump Association)

### The CEN Heat Pump KEYMARK



The Heat Pump KEYMARK is a full certificate supporting the quality of heat pumps in the European market. The Heat Pump KEYMARK is a voluntary, independent, European certification mark (ISO Type 5 Certification) for all heat pumps, combination heat pumps, and hot water heaters (as covered by Ecodesign, EU Regulation 813/2013 and 814/2013). General's Air to Water<sup>5</sup> has acquired the KEYMARK certificate<sup>6</sup>.

<sup>5</sup>: R32 refrigerant comfort model only  
<sup>6</sup>: Learn more about the validity of the mark at [www.heatpumpkeymark.com/about/](http://www.heatpumpkeymark.com/about/)

# AIR TO WATER Lineup

Type	Series	Refrigerant	Model	Power Source	Capacity								Approval				
					5kw	6kw	8kw	10kw	11kw	12kw	14kw	16kw	17kw	CEN KEYMARK	EHPA		
Split type	Comfort series Wall-mounted type	R32 Heating*		Single phase, ~230 V, 50 Hz	WSHA050ML3 WOHA060KLT	WSHA080ML3 WOHA060KLT	WSHA080ML3 WOHA080KLT	WSHA100ML3 WOHA100KLT									
	Comfort series DHW Integrated type	R32 Heating*		Single phase, ~230 V, 50 Hz	WGHA050ML3 WOHA060KLT	WGHA080ML3 WOHA060KLT	WGHA080ML3 WOHA080KLT	WGHA100ML3 WOHA100KLT									
	High Power series Wall-mounted type	R32 Heating		Single phase, ~230 V, 50 Hz				WSHG140MQ6 WOHG100MQL	WSHG140MQ6 WOHG121MQL	WSHG140MQ6 WOHG140MQL							
				3-phase, ~400 V, 50 Hz					WSHK140MQ9 WOHK121MQL	WSHK140MQ9 WOHK140MQL							
		R410A Heating*		Single phase, ~230 V, 50 Hz				WSHG140DG WOHG112LHT		WSHG140DG WOHG140LCTA							
				3-phase, ~400 V, 50 Hz				WSHG140DG WOHK112LCTA		WSHG140DG WOHK140LCTA	WSHG140DG WOHK160LCTA						
	High Power series DHW Integrated type	R32 Heating		Single phase, ~230 V, 50 Hz				WGHG140MQ6-19 WOHG100MQL	WGHG140MQ6-19 WOHG121MQL	WGHG140MQ6-19 WOHG140MQL							
				3-phase, ~400 V, 50 Hz					WGHK140MQ9-19 WOHK121MQL	WGHK140MQ9-19 WOHK140MQL							
		R410A Heating*		Single phase, ~230 V, 50 Hz				WGHG140DG WOHG112LHT		WGHG140DG WOHG140LCTA							
				3-phase, ~400 V, 50 Hz				WGHG140DG WOHK112LCTA		WGHG140DG WOHK140LCTA	WGHG140DG WOHK160LCTA						
	Super High Power series Wall-mounted type	R410A Heating*		Single phase, ~230 V, 50 Hz									WSHG160DJ6 WOHG160LJL				
	Super High Power series DHW Integrated type	R410A Heating*		Single phase, ~230 V, 50 Hz									WGHG160DJ6 WOHG160LJL				

\*Cooling is available by using the option

## EHPA Quality Label



General's Air to Water<sup>2</sup> has acquired the EHPA Quality Label<sup>3</sup> through testing in accordance with the International Standards EN14511 and EN17025. The EHPA Quality Label<sup>3</sup> is a label that shows the end-consumer a quality heat pump unit on the market.

<sup>2</sup>: 3-phase high power series only  
<sup>3</sup>: Learn more about the validity of the mark at [www.ehpa.org/quality/quality-label/](http://www.ehpa.org/quality/quality-label/)

## SG ready Label



SG ready is a label issued to heat pumps and their control technologies that meet the requirements set by BWP<sup>4</sup>, and technologies that conform to their standards can be integrated into a smart grid. SG ready labeled heat pumps receive signals from the power grid and PV systems with regard to energy and renewable energy sources such as wind, solar, and water. All of General's heat pump series are SG ready compatible.

<sup>4</sup>: BWP: Bundesverband Wärmepumpe e. V (Federal German Heat Pump Association)

## The CEN Heat Pump KEYMARK



The Heat Pump KEYMARK is a full certificate supporting the quality of heat pumps in the European market. The Heat Pump KEYMARK is a voluntary, independent, European certification mark (ISO Type 5 Certification) for all heat pumps, combination heat pumps, and hot water heaters (as covered by Ecodesign, EU Regulation 813/2013 and 814/2013). General's Air to Water<sup>5</sup> has acquired the KEYMARK certificate<sup>6</sup>.

<sup>5</sup>: R32 refrigerant comfort model only  
<sup>6</sup>: Learn more about the validity of the mark at [www.heatpumpkeymark.com/about/](http://www.heatpumpkeymark.com/about/)



# Monobloc Type

Comfort series

Fits into Your Life



Monobloc type with fewer pipe works and easy installation. It provides a wide variety of solutions to meet the usage environment.

## Aesthetic and Compact Design


By changing from the conventional two-fan system to a large-diameter single-fan system, we have been able to keep the height down. Because it is lower than a house window, you won't have any trouble finding a place to install the outdoor unit.



8 & 10 kW Classes

### System configuration example

No refrigerant pipe is required as outdoor unit and indoor unit (or tank) are connected by water pipe



\*System configuration when using Wall-mounted indoor unit


# High Energy Efficiency

## Energy Efficiency Class



\*Temperature application: Heating temp. 35°C

Plate heat exchanger with high heat exchange performance improves energy-related product performance, achieving high energy efficiency. All classes achieved top rank A+++\* energy efficiency class.



\* Value when the control box is connected



Compact & High efficiency Plate heat exchanger

Transmitting the heat of the Refrigerant to the Water.




5 kW class



## Inverter Technology

Inverter-equipped models operate at a capacity suited to the heat load. Because they can respond to heat loads in details inverter-equipped models are more economical and comfortable than non-inverter models. Compared to a non-inverter, it reaches the set temperature more quickly, operates at the minimum capacity and responds to slight changes in water temperature. The range of water temperature fluctuation is small, and a comfortable temperature is maintained.


Inverter technology controls temperatures precisely.



## Technology to Achieve High Efficiency

### High-precision parts


The precision machining of parts has improved the degree of adhesion between parts. Refrigerant leakage from gaps has been reduced, leading to improved compression efficiency and high-efficiency operation. In addition, the contact surfaces between parts have been smoothed and the amount of wear has been reduced, resulting in stable performance over a long period of time.



2 Cylinder rotary compressor

### High-magnetic flux motor

Copper and iron losses are thoroughly suppressed to realize high magnetic flux of the motor. The high magnetic flux produces stronger torque than ever before. Thanks to this, operation with less current is possible, bringing out high-efficiency operation.



### Smooth gas flow


The arrangement of parts that do not obstruct refrigerant flow in the compressor leads to highly efficient operation. Broad interpretation of the optimization of refrigerant flow paths has resulted in about 13 patents.



Larger fan

## Low Noise Operation

In the outdoor unit, a larger fan and a sound-insulating structure in the compressor part reduce the maximum operating noise. The Monobloc outdoor unit can operate silently at 52 dB(A)\* with high energy efficiency. \*050 models




Quiet operation  
**52 dB(A)**  
050 model

## Durability and Reliability

We take care to ensure that our products can be used by our customers for a long time. We have taken measures to reduce damage to our products even in the event of problems with the installation environment or during operation.



8 & 10 kW classes



### Pressure Switch

The pressure switch equipped on the refrigerant cycle protects the system from malfunction that may be caused by abnormal refrigerant pressure.



### Silicon Coating of PCBs


The silicon coating protects the PCBs and their components from damage caused by small animals living in the electrical box and salt.

### Optimized shaft design

- The stress on specific parts is reduced, reducing the risk of wear and damage
- Vibration during rotation is reduced, reducing wear and fatigue damage, and ultimately improving durability

### DLC coating vane

- It has a very high hardness and low wear coefficient, and shows excellent resistance to wear
- It is chemically stable and has excellent resistance to various working fluids and environmental conditions, so it protects the vanes from corrosion and chemical degradation, contributing to a longer lifespan



2 Cylinder rotary compressor

### Technology to Increase Durability

#### Optimal lubricant

- Prevents friction and heating of parts, improving durability
- Contains rust-proofing and antioxidant agents, protecting metal parts from corrosion and preventing breakdowns and performance degradation
- Reduces impact between parts, suppresses vibration, and prevents excessive stress on parts, improving durability



\*The values in the pictures are examples.

## Service Monitor Tool

UTY-ASSXZ1



### Bluetooth Communication

AIRSTAGE Service Monitor Tool can diagnose using a smart device and reduce the working time compared with diagnosis by PC. No need to connect a PC making diagnosis easier even in narrow spaces.

### Application with simple design

Application for smart devices has been released. The stylish design makes the application easy to use for everyone.



AIRSTAGE Service Monitor Tool

#### Refrigerant cycle diagram display

The operating status can be displayed with a simple, clear diagram\*2 on the smart device. It reduces the time for diagnosis and makes diagnosis easier. It can complement abundant experience and advanced knowledge of refrigerant cycle. This shortens the training time for service personnel.

\*2: List and graph displays are also available

### Compact and Lightweight Design

This model is easy to carry by compact and lightweight design. The service personnel can visit the maintenance site with small luggage.



#### Function List

		UTY-ASSXZ1	
Product specification	Installation	Outdoor unit PCB	
	Communication	Bluetooth	
Function	Product distinction	●	
	Signal-type distinction	●	
		List	●
	Operating status display	Graph	●
		Refrigerant cycle diagram	●
Operating history records		●	
Adapter firmware update	●		
Adapter status monitoring	●		
Input and output of history data	●		

#### Specifications


		UTY-ASSXZ1
Dimensions (H x W x D) (mm)		20 x 35 x 60 (adapter)
Communication cable (cm)		60
Weight (g)		25 (adapter)
Communication method		Bluetooth 5.3
Max. communication distance (m)		10*3
Compatible device		Android8.0, iOS17 or later

\*3: Depends on the environment

## Serviceability and Maintainability

### Easy Pipe Work

No refrigerant pipe work is required as the outdoor unit is an integrated unit. The hot water unit comes standard with the outdoor unit. Installation requires only hydraulic connection work, making installation easy.



### Easy Installation


Wire connections can be made simply by removing the side panel, so installation work can be easily carried out from a single direction. The compact, lightweight panel is easy to remove.



### Improved Workability

- The indoor unit is equipped with a buffer tank, DHW connection 3-way valve\*, as well as an expansion tank and backup heater
- This improves system reliability and ease of installation

\*Wall-mounted only



## Useful Features

Features	Explanation
<b>Quick recovery from defrosting</b>	Maintains room temperature by boost start operation during defrosting
<b>Auto changeover</b>	When auto mode is selected, the system automatically switches between cooling and heating modes depending on the outside temperature.
<b>2-zone independent control</b>	2-zone independent control
<b>Backup heater operation</b>	Backup heater maintains a comfortable room temperature even when the outside temperature is low. It is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.
<b>Peak cut function</b>	Sets the peak current value to reduce power consumption. Mode 1 -> 100% Mode 2 -> 75% Mode 3 -> 50% Mode 4 -> Almost 0%
<b>Anti-Freezing function</b>	When the outside temperature drops below a specified level, the compressor will self-activate and water will also be automatically circulated to prevent freezing.
<b>Anti-Legionella function</b>	Prevents the growth of Legionella bacteria in the DHW tank to supply safe and clean hot water at all times.
<b>Emergency operation</b>	If an outdoor unit fails to operate, a built-in backup heater or an external boiler is activated to supply an uninterrupted supply of hot water to the house.



**Monobloc type**  
Comfort series (Control box type)

Indoor unit:  
**UTW-SCBHC**

Outdoor unit:  
**WPHG050KRF / WPHG080KRF**  
**WPHG100KRF**



**Specifications**


Model Name	Indoor unit Outdoor unit	Control box						
		UTW-SCBHC WPHG050KRF	UTW-SCBHC WPHG080KRF	UTW-SCBHC WPHG100KRF				
Capacity Range		5	8	10				
7°C/35°C floor heating*1	Heating capacity (Max.)	5.00 (8.31)	8.00 (13.28)	10.00 (15.20)				
	Input power (Max.)	0.97 (1.97)	1.54 (2.96)	2.05 (3.53)				
	COP (Max.)	5.15 (4.22)	5.19 (4.48)	4.88 (4.30)				
7°C/55°C radiator*1	Heating capacity (Max.)	5.00 (7.21)	8.00 (10.60)	10.00 (11.56)				
	Input power (Max.)	1.64 (2.44)	2.62 (3.51)	3.36 (3.94)				
	COP (Max.)	3.04 (2.95)	3.05 (3.02)	2.98 (2.93)				
-7°C/55°C radiator*1	Heating capacity (Max.)	4.80 (5.36)	7.50 (8.15)	8.50 (9.00)				
	Input power (Max.)	2.25 (2.57)	3.50 (3.94)	3.97 (3.94)				
	COP (Max.)	2.13 (2.09)	2.14 (2.07)	2.14 (2.93)				
35°C/18°C cooling mode*1	Cooling capacity (Max.)	5.45 (6.55)	7.79 (10.87)	9.40 (10.87)				
	Input power (Max.)	1.25 (1.82)	1.69 (3.22)	2.40 (3.22)				
	EER (Max.)	4.35 (3.60)	4.62 (3.37)	3.91 (3.37)				
<b>Space heating characteristics**</b>								
Temperature application	°C	55	35	55	35	55	35	
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++	
Rated heat output (P <sub>rated</sub> )	kW	6	6	9	9	10	10	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	143	200	144	205	146	206	
Annual energy consumption	kWh	3,110	2,364	4,880	3,571	5,480	4,018	
Sound power level*3	Outdoor unit	dB(A)	52	52	56	56	57	57
<b>Indoor unit specifications</b>								
Power source		Single phase, 230 V, 50 Hz						
Dimensions H × W × D	mm	483 × 370 × 222						
Weight (Net)	kg	10						
<b>Outdoor unit specifications</b>								
Power source		Single phase, 230 V, 50 Hz						
Current	Max.	A	14.6	19.1	20.6			
Water flow temperature range	Max.	°C	60	60	60			
Dimensions H × W × D	mm	798 × 1,080 × 480						
Weight (Net)	kg	85						
Refrigerant	Type (Global Warming Potential)		R32 (675)			R32 (675)		
	Charge	kg	0.88			1.47		
Connection pipe	Diameter	mm	Ø25.4			Ø25.4		
Operating range	Heating	°C	-20 to 35			-20 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalw.com/global/support/downloads/search/](http://www.generalw.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


**Dimensions**

(Unit: mm)


**Control box:**  
UTW-SCBHC




**Wall Mounted:**  
WSHP100KR3




**DHW Integrated:**  
WGHP100KR3-19



**Outdoor unit:**  
WPHG050KRF



WPHG080KRF/WPHG100KRF



**Monobloc type**  
Comfort series (Wall-mounted type / DHW Integrated type)

Indoor unit:  
**WSHP100KR3**  
**WGHP100KR3-19**

Outdoor unit:  
**WPHG050KRF / WPHG080KRF**  
**WPHG100KRF**



**Specifications**

Model Name	Indoor unit Outdoor unit	Wall Mounted			DHW Integrated			
		WSHP100KR3 WPHG050KRF	WSHP100KR3 WPHG080KRF	WSHP100KR3 WPHG100KRF	WGHP100KR3-19 WPHG050KRF	WGHP100KR3-19 WPHG080KRF	WGHP100KR3-19 WPHG100KRF	
Capacity Range		5	8	10	5	8	10	
7°C/35°C floor heating*1	Heating capacity (Max.)	5.00 (8.10)	8.00 (13.07)	10.00 (14.99)	5.00 (8.10)	8.00 (13.07)	10.00 (14.99)	
	Input power (Max.)	1.00 (2.00)	1.57 (3.08)	2.13 (3.64)	1.00 (2.00)	1.57 (3.08)	2.13 (3.64)	
	COP (Max.)	4.99 (4.05)	5.08 (4.24)	4.70 (4.11)	4.99 (4.05)	5.08 (4.24)	4.70 (4.11)	
7°C/55°C radiator*1	Heating capacity (Max.)	5.00 (6.86)	8.00 (10.24)	10.00 (11.20)	5.00 (6.86)	8.00 (10.24)	10.00 (11.20)	
	Input power (Max.)	1.72 (2.47)	2.62 (3.55)	3.40 (3.99)	1.72 (2.47)	2.62 (3.55)	3.40 (3.99)	
	COP (Max.)	2.91 (2.77)	3.05 (2.89)	2.94 (2.81)	2.91 (2.77)	3.05 (2.89)	2.94 (2.81)	
-7°C/55°C radiator*1	Heating capacity (Max.)	4.80 (4.90)	7.50 (7.69)	8.50 (8.54)	4.80 (4.90)	7.50 (7.69)	8.50 (8.54)	
	Input power (Max.)	2.51 (2.62)	3.62 (3.99)	4.11 (4.35)	2.51 (2.62)	3.62 (3.99)	4.11 (4.35)	
	COP (Max.)	1.91 (1.87)	2.07 (1.93)	2.07 (1.96)	1.91 (1.87)	2.07 (1.93)	2.07 (1.96)	
35°C/18°C cooling mode*1	Cooling capacity (Max.)	5.35 (6.42)	7.69 (10.75)	9.30 (10.75)	5.35 (6.42)	7.69 (10.75)	9.30 (10.75)	
	Input power (Max.)	1.26 (1.85)	1.72 (3.32)	2.47 (3.32)	1.26 (1.85)	1.72 (3.32)	2.47 (3.32)	
	EER (Max.)	4.23 (3.48)	4.47 (3.24)	3.77 (3.24)	4.23 (3.48)	4.47 (3.24)	3.77 (3.24)	
<b>Space heating characteristics**</b>								
Temperature application	°C	55	35	55	35	55	35	
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++	
Rated heat output (P <sub>rated</sub> )	kW	6	6	9	9	10	10	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	133	189	139	195	141	195	
Annual energy consumption	kWh	3,355	2,503	5,078	3,764	5,685	4,269	
Sound power level*3	Outdoor unit	dB(A)	52	52	56	56	57	57
<b>Indoor unit specifications</b>								
Power source		Single phase, 230 V, 50 Hz			Single phase, 230 V, 50 Hz			
Dimensions H × W × D	mm	737 × 448 × 469			1755 × 598 × 623			
Weight (Net)	kg	34.0			130.0			
Water circulation	Min./Max.	L/min			L/min			
DHW tank volume	L	8.5			14.5			
Buffer tank capacity	L	16			16			
Expansion vessel capacity	L	12			12			
Water flow temperature range	Max.	°C			°C			
Water pipe connection diameter	Flow/Return	mm			mm			
Electrical heater capacity	Heating/DHW	kW			kW			
Declared load profile		-			L			
Efficiency ηDHW	%	-			124			
Heating up time		-			1h45min			
COP(EN16147)		-			3.10			
<b>Outdoor unit specifications</b>								
Power source		Single phase, 230 V, 50 Hz			Single phase, 230 V, 50 Hz			
Current	Max.	A	14.6	19.1	20.6	14.6	20.6	
Water flow temperature range	Max.	°C	60	60	60	60	60	
Dimensions H × W × D	mm	798 × 1,080 × 480			1,008 × 1,080 × 480			
Weight (Net)	kg	85			109			
Refrigerant	Type (Global Warming Potential)		R32 (675)			R32 (675)		
	Charge	kg	0.88			1.47		
Connection pipe	Diameter	mm	Ø25.4			Ø25.4		
Operating range	Heating	°C	-20 to 35			-20 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalw.com/global/support/downloads/search/](http://www.generalw.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.




**Split Type**  
Comfort series  
High Power series



**Split Type**  
High Power series  
Super High Power series

This is a split type that exchanges heat from Air to Water inside the indoor unit.

A wide range of products to suit regional characteristics, family structures, and usage patterns. We provide a variety of products to meet the needs of customers from the heating-centered high power series to the reasonably priced compact series.



\*Indoor unit : Wall-mounted

## High Water Flow Temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C\*.

\* The Super High Power Series and The R410A High Power Series only. The R32 High Power Series is rated for -15°C. The Comfort Series is rated for -10°C.




NEW High Power series

### High Power series & Super High Power series



### NEW High Power series



### Comfort series



\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater

## High COP



Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

### Seasonal space heating energy efficiency ( $\eta_s$ )



\*Conditions: Outdoor Temp. 7°C, Heating Temp. 35°C



#### Energy efficiency class



#### Energy efficiency class




# High Energy Efficiency

## Outdoor Unit Technology to Achieve high Efficiency


### High-magnetic flux motor

Copper and iron losses are thoroughly suppressed to realize high magnetic flux of the motor. The high magnetic flux produces stronger torque than ever before. Thanks to this, operation with less current is possible, bringing out high-efficiency operation.



### Smooth gas flow

The arrangement of parts that do not obstruct refrigerant flow in the compressor leads to highly efficient operation. Broad interpretation of the optimization of refrigerant flow paths has resulted in about 13 patents.



2 Cylinder rotary compressor

### High-precision parts

The precision machining of parts has improved the degree of adhesion between parts. Refrigerant leakage from gaps has been reduced, leading to improved compression efficiency and high-efficiency operation. In addition, the contact surfaces between parts have been smoothed and the amount of wear has been reduced, resulting in stable performance over a long period of time.

### NEW High power series outdoor unit




Larger fan

### Low Noise Operation

In the outdoor unit, a larger fan and a sound-insulating structure in the compressor part reduce the maximum operating noise. The Split type High power Series outdoor unit can operate silently at 56 dB(A)\* with high energy efficiency. \*10/12 kW models




### Comfort series outdoor unit



- DC Inverter**  
DC inverter provides smooth water temperature control.
- DC Fan Motor**  
High-performance, high-efficiency small DC fan motor mounted
- DC Twin-Rotary Compressor**  
High-efficiency DC twin-rotary compressor

### Twin-Rotary Compressor with Linear Control Injection Port

The compressor achieves a high condensing temperature without overheating the discharge gas temperature due to the Linear control injection process used during compression. This makes the condensing temperature higher than in a normal circuit. Higher water temperatures can be achieved by controlling the injection volume according to usage conditions.




## Indoor Unit Technology to Achieve high Efficiency



### Class A Pump

Energy-saving pump with the ability to adjust the flow rate and pressure to a constant level

### High-durability coaxial heat exchanger



### Stainless Steel Buffer Tank


Energy-saving performance has also been improved. The buffer tank has anti-corrosion protection thanks to stainless steel material.



## Durability and Reliability



We take care to ensure that our products can be used by our customers for a long time. We have taken measures to reduce damage to our products even in the event of problems with the installation environment or during operation.



### Pressure Switch

The pressure switch equipped on the refrigerant cycle protects the system from malfunction that may be caused by abnormal refrigerant pressure.

### Silicon Coating of PCBs


The silicon coating protects the PCBs and their components from damage caused by small animals living in the electrical box and salt.



## Technology to Increase Durability

### Optimal bearings

Reduced stress on specific parts of the body reduces the risk of wear and tear. Reduced vibration during rotation reduces wear and fatigue damage, resulting in increased durability.



2 Cylinder rotary compressor  
NEW High power series

### Coated vane

- Very high hardness and low coefficient of wear, providing excellent resistance to abrasion. Scientifically stable and highly resistant to a wide range of working fluids and environmental conditions, it protects vanes from corrosion and chemical degradation, contributing to longer service life.

### Optimal lubricating oil


- Improves durability by preventing friction and heating of parts
- Contains rust inhibitors and antioxidants to protect metal parts from corrosion, which can cause failure and loss of performance.
- Reduces shock and vibration between parts, preventing overstressing of parts and increasing durability

## Serviceability and Maintainability

### Improved Workability

- The indoor unit is equipped with a buffer tank, DHW connection 3-way valve\*, as well as an expansion tank and backup heater
- This improves system reliability and ease of installation


\*Wall-mounted only



There is no need to connect pumps, valves, etc. as separate parts. The fewer connections there are between the pipe and the parts, the fewer problems there will be.

## Useful Features

Features	Explanation
Quick recovery from defrosting	Maintains room temperature by boost start operation during defrosting
Auto changeover	When cooling mode is selected, the system automatically switches between cooling and heating modes depending on the outside temperature.
2-zone independent control	2-zone independent control
Backup heater operation	Backup heater maintains a comfortable room temperature even when the outside temperature is low. It is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.
Peak cut function	Sets the peak current value to reduce power consumption. Mode 1 -> 100% Mode 2 -> 75% Mode 3 -> 50% Mode 4 -> Almost 0%
Anti-Freezing function	When the outside temperature drops below a specified level, the compressor will self-activate and water will also be automatically circulated to prevent freezing.
Anti-Legionella function	Prevents the growth of Legionella bacteria in the DHW tank to supply safe and clean hot water at all times.
Emergency operation	If an outdoor unit fails to operate, a built-in backup heater or an external boiler is activated to supply an uninterrupted supply of hot water to the house.



## Smart Control

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.

**Split type**  
Comfort series (Wall-mounted type)

**Indoor unit:**  
WSHA050ML3 / WSHA080ML3 / WSHA100ML3  
**Outdoor unit:**  
WOHA060KLT / WOHA080KLT / WOHA100KLT



**Specifications**


Model Name	Indoor unit	Outdoor unit	WSHA050ML3	WSHA080ML3	WSHA080ML3	WSHA100ML3				
Capacity Range			5	6	8	10				
7°C/35°C floor heating*1	Heating capacity (Max.)	kW	4.50 (7.64)	5.50 (8.93)	7.50 (9.64)	9.50 (15.29)				
	Input power (Max.)		0.949 (1.80)	1.18 (2.24)	1.69 (2.46)	2.11 (3.89)				
	COP (Max.)		4.74 (4.24)	4.65 (3.99)	4.43 (3.92)	4.50 (3.93)				
2°C/35°C floor heating*1	Heating capacity	kW	4.50	5.30	6.30	9.30				
	Input power		1.33	1.65	1.96	3.08				
	COP		3.39	3.22	3.21	3.02				
-7°C/35°C floor heating*1	Heating capacity (Max.)	kW	4.40 (4.97)	5.00 (6.13)	5.70 (7.05)	8.90 (10.40)				
	Input power (Max.)		1.59 (1.67)	1.90 (2.12)	2.13 (2.55)	3.36 (3.62)				
	COP (Max.)		2.76 (2.98)	2.63 (2.89)	2.68 (2.76)	2.65 (2.87)				
-7°C/55°C Radiator*1	Heating capacity (Max.)	kW	3.90 (4.24)	4.25 (4.86)	5.30 (5.85)	8.00 (8.00)				
	Input power (Max.)		2.11 (2.25)	2.25 (2.69)	2.79 (3.26)	4.10 (4.10)				
	COP (Max.)		1.85 (1.88)	1.89 (1.81)	1.90 (1.79)	1.95 (1.95)				
<b>Space heating characteristics**</b>										
Temperature application	°C		55	35	55	35	55	35	55	35
Energy efficiency class			A++	A+++	A++	A+++	A++	A+++	A++	A+++
Rated heat output (P <sub>rated</sub> )	kW		5	5	6	6	7	8	9	9
Seasonal space heating energy efficiency (η <sub>s</sub> )	%		125	175	125	175	128	177	130	178
Annual energy consumption	kWh		3,035	2,322	3,411	2,594	3,903	2,982	5,083	3,875
Sound power level*3	Indoor unit	dB(A)	40	-	40	-	40	-	40	-
	Outdoor unit		57	-	57	-	60	-	62	-
<b>Indoor unit specifications</b>										
Power source	Single phase, ~230 V, 50 Hz									
Dimensions H × W × D	mm		847 × 450 × 493	847 × 450 × 493	847 × 450 × 493	847 × 450 × 493				
Weight (Net)	kg		47	47	47	47				
Water circulation	Min./Max.	L/min	7.6/22.0	8.5/22.0	10.0/22.0	13.2/30.0				
Buffer tank capacity	L		16	16	16	16				
Expansion vessel capacity	L		8	8	8	8				
Water flow temperature range	Max.	°C	55	55	55	55				
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4				
Electrical heater capacity	Heating	kW	3.0	3.0	3.0	3.0				
<b>Outdoor unit specifications</b>										
Power source	Single phase, ~230 V, 50 Hz									
Current	Max.	A	13.0	13.0	18.0	19.0				
Dimensions H × W × D	mm		632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	998 × 940 × 320				
Weight (Net)	kg		39	39	42	62				
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)				
Additional refrigerant charge	Charge	kg	0.97	0.97	1.02	1.63				
		g/m	25	25	25	20				
Connection pipe	Diameter	Liquid	mm	6.35	6.35	6.35	9.52			
		Gas		12.70	12.70	12.70	15.88			
	Length	Min./Max.	m	3/30	3/30	3/30	3/30			
		(Pre-charge)		15	15	15	20			
Height difference	Max.	m	20	20	20	20				
			20	20	20	20				
Operating range	Heating	°C	-20 to 35	-20 to 35	-20 to 35	-20 to 35				

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalw.com/global/support/downloads/search/](http://www.generalw.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


**Dimensions**

(Unit: mm)

**Indoor Unit:**  
WSHA050ML3/WSHA080ML3/WSHA100ML3



WGHA050ML3/WGHA080ML3/WGHA100ML3



**Split type**  
Comfort series (DHW Integrated type)

**Indoor unit:**  
WGHA050ML3 / WGHA080ML3 / WGHA100ML3  
**Outdoor unit:**  
WOHA060KLT / WOHA080KLT / WOHA100KLT




**Specifications**


Model Name	Indoor unit	Outdoor unit	WGHA050ML3	WGHA080ML3	WGHA080ML3	WGHA100ML3				
Capacity range			5	6	8	10				
7°C/35°C floor heating*1	Heating capacity (Max.)	kW	4.50 (7.64)	5.50 (8.93)	7.50 (9.64)	9.50 (15.29)				
	Input power (Max.)		0.949 (1.80)	1.18 (2.24)	1.69 (2.46)	2.11 (3.89)				
	COP (Max.)		4.74 (4.24)	4.65 (3.99)	4.43 (3.92)	4.50 (3.93)				
2°C/35°C floor heating*1	Heating capacity	kW	4.50	5.30	6.30	9.30				
	Input power		1.33	1.65	1.96	3.08				
	COP		3.39	3.22	3.21	3.02				
-7°C/35°C floor heating*1	Heating capacity (Max.)	kW	4.40 (4.97)	5.00 (6.13)	5.70 (7.05)	8.90 (10.40)				
	Input power (Max.)		1.59 (1.67)	1.90 (2.12)	2.13 (2.55)	3.36 (3.62)				
	COP (Max.)		2.76 (2.98)	2.63 (2.89)	2.68 (2.76)	2.65 (2.87)				
-7°C/55°C Radiator*1	Heating capacity (Max.)	kW	3.90 (4.24)	4.25 (4.86)	5.30 (5.85)	8.00 (8.00)				
	Input power (Max.)		2.11 (2.25)	2.25 (2.69)	2.79 (3.26)	4.10 (4.10)				
	COP (Max.)		1.85 (1.88)	1.89 (1.81)	1.90 (1.79)	1.95 (1.95)				
<b>Space heating characteristics**</b>										
Temperature application	°C		55	35	55	35	55	35		
Energy efficiency class			A++	A+++	A++	A+++	A++	A+++		
Rated heat output (P <sub>rated</sub> )	kW		5	5	6	6	7	8	9	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%		125	175	125	175	128	177	130	178
Annual energy consumption	kWh		3,035	2,322	3,411	2,594	3,903	2,982	5,083	3,875
Sound power level*3	Indoor unit	dB(A)	40	-	40	-	40	-	40	-
	Outdoor unit		57	-	57	-	60	-	62	-
<b>Domestic hot water characteristics**</b>										
Load profile			L	L	L	L				
Energy efficiency class			A+	A+	A+	A+				
Energy efficiency (η <sub>wh</sub> )	%		130	130	130	130				
Annual electricity consumption	kWh		793	793	793	793				
<b>Indoor unit specifications</b>										
Power source	Single phase, ~230 V, 50 Hz									
Dimensions H × W × D	mm		1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700				
Weight (Net)	kg		145	145	145	145				
Water circulation	Min./Max.	L/min	7.6/22.0	8.5/22.0	10.0/22.0	13.2/30.0				
DHW tank volume	L		190	190	190	190				
Electrical heater capacity	Heating	kW	3.0	3.0	3.0	3.0				
	DHW		1.5	1.5	1.5	1.5				
Buffer tank capacity	L		16	16	16	16				
Expansion vessel capacity	L		8	8	8	8				
Water flow temperature range	Max.	°C	55	55	55	55				
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4				
Hot water pipe connection diameter	mm		Ø19.05	Ø19.05	Ø19.05	Ø19.05				
<b>Outdoor unit specifications</b>										
Power source	Single phase, ~230 V, 50 Hz									
Current	Max.	A	13.0	13.0	18.0	19.0				
Dimensions H × W × D	mm		632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	998 × 940 × 320				
Weight (Net)	kg		39	39	42	62				
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)				
Additional refrigerant charge	Charge	kg	0.97	0.97	1.02	1.63				
		g/m	25	25	25	20				
Connection pipe	Diameter	Liquid	mm	6.35	6.35	6.35	9.52			
		Gas		12.70	12.70	12.70	15.88			
	Length	Min./Max.	m	3/30	3/30	3/30	3/30			
		(Pre-charge)		15	15	15	20			
Height difference	Max.	m	20	20	20	20				
			20	20	20	20				
Operating range	Heating	°C	-20 to 35	-20 to 35	-20 to 35	-20 to 35				

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalw.com/global/support/downloads/search/](http://www.generalw.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


**Outdoor Unit:**  
WOHA060KLT



WOHA080KLT



WOHA100KLT



**Split type**  
High power series (Wall-mounted type)

**Indoor unit:**  
**WSHG140MQ6**  
[3-phase] WSHK140MQ9

**Outdoor unit:**  
**WOHG100MQL / WOHG121MQL / WOHG140MQL**  
[3-phase] WOHK121MQL / WOHK140MQL



**Specifications**


Model Name	Indoor unit		Wall Mounted										
	Outdoor unit		WSHG140MQ6	WSHG140MQ6	WSHG140MQ6	WSHK140MQ9	WSHK140MQ9						
Capacity Range			10	12	14	12	14						
7°C/35°C floor heating*1	Heating capacity (Max.)	kW	10.08 (15.3)	12.55 (16.2)	14.47 (17.8)	12.55 (16.2)	14.47 (17.8)						
	Input power (Max.)		2.18 (3.54)	2.69 (3.80)	3.36 (4.16)	2.69 (3.80)	3.36 (4.16)						
	COP (Max.)		4.62 (4.33)	4.67 (4.25)	4.31 (4.28)	4.67 (4.25)	4.31 (4.28)						
7°C/55°C radiator*1	Heating capacity (Max.)	kW	8.24 (12.3)	9.16 (13.7)	10.09 (15.5)	9.16 (13.7)	10.09 (15.5)						
	Input power (Max.)		2.79 (4.15)	3.06 (4.72)	3.36 (5.41)	3.06 (4.72)	3.36 (5.41)						
	COP (Max.)		2.95 (2.96)	2.99 (2.91)	3.00 (2.87)	2.99 (2.91)	3.00 (2.87)						
-7°C/55°C radiator*1	Heating capacity (Max.)	kW	7.10 (9.1)	8.63 (10.2)	10.28 (10.5)	8.63 (10.2)	10.28 (10.5)						
	Input power (Max.)		3.30 (4.26)	4.03 (4.84)	4.74 (4.99)	4.03 (4.84)	4.74 (4.99)						
	COP (Max.)		2.15 (2.14)	2.14 (2.12)	2.17 (2.11)	2.14 (2.12)	2.17 (2.11)						
<b>Space heating characteristics*2</b>			°C		55	35	55	35	55	35	55	35	
Energy efficiency class			A++	A+++	A++	A+++	A++	A+++	A++	A+++	A++	A+++	
Rated heat output (P <sub>rated</sub> )			kW	8.2	8.5	9.8	10.1	11.4	11.7	9.8	10.1	11.4	11.7
Seasonal space heating energy efficiency (η <sub>s</sub> )			%	131	183	135	183	137	185	135	183	137	185
Annual energy consumption			kWh	5,060	3,771	5,879	4,476	6,717	5,132	5,879	4,476	6,717	5,132
Sound power level*3			Outdoor unit	dB(A)		56	56	58	56	56	58	58	
<b>Indoor unit specifications</b>													
Power source			Single phase, 230 V, 50 Hz			3-phase, ~400 V, 50 Hz							
Dimensions H × W × D			mm		750 × 448 × 469	750 × 448 × 469	750 × 448 × 469	750 × 448 × 469	750 × 448 × 469				
Weight (Net)			kg		46	46	46	46	46				
Water circulation			Min./Max.		L/min	10/42	10/42	10/42	10/42				
DHW tank volume			L		-	-	-	-	-				
Buffer tank capacity			L		15	15	15	15	15				
Expansion vessel capacity			L		12	12	12	12	12				
Water flow temperature range			Max.		°C	60	60	60	60				
Water pipe connection diameter			Flow/Return		mm	Ø19.05/Ø19.05	Ø19.05/Ø19.05	Ø19.05/Ø19.05	Ø19.05/Ø19.05				
Electrical heater capacity			Heating		kW	6	6	6	9				
<b>Outdoor unit specifications</b>													
Power source			Single phase, 230 V, 50 Hz			3-phase, ~400 V, 50 Hz							
Current			Max.		A	19.5	22.0	25.0	8.8	9.8			
Water flow temperature range			Max.		°C	60	60	60	60	60			
Dimensions H × W × D			mm		1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480				
Weight (Net)			kg		96	96	102	96	102				
Refrigerant			Type (Global Warming Potential)		R32		R32	R32	R32				
Additional refrigerant charge			Charge		kg		1.40	1.40	1.63	1.40	1.63		
Connection pipe			Diameter		Liquid		mm		Ø6.35	Ø6.35	Ø6.35		
					Gas				Ø12.7	Ø12.7	Ø12.7		
			Length		Min./Max.		m		3/25	3/25	3/25		
			Length (Pre-charge)		m				15	15	15		
			Height difference		Max.		m		20	20	20		
Operating range			Heating		°C				-25 to 35	-25 to 35	-25 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalwv.com/global/support/downloads/search/](http://www.generalwv.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


**Dimensions**

(Unit: mm)

**Wall Mounted:**  
Single phase: WSHG140MQ6  
3-phase: WSHK140MQ9



**DHW Integrated:**  
Single phase: WGHG140MQ6-19  
3-phase: WGHK140MQ9-19



**Split type**  
High power series (DHW Integrated type)

**Indoor unit:**  
**WGHG140MQ6-19**  
[3-phase] WGHK140MQ9-19

**Outdoor unit:**  
**WOHG100MQL / WOHG121MQL / WOHG140MQL**  
[3-phase] WOHK121MQL / WOHK140MQL




**Specifications**

Model Name	Indoor unit		DHW Integrated										
	Outdoor unit		WGHG140MQ6-19	WGHG140MQ6-19	WGHG140MQ6-19	WGHK140MQ9-19	WGHK140MQ9-19						
Capacity Range			10	12	14	12	14						
7°C/35°C floor heating*1	Heating capacity (Max.)	kW	10.08 (15.3)	12.55 (16.2)	14.47 (17.8)	12.55 (16.2)	14.47 (17.8)						
	Input power (Max.)		2.18 (3.54)	2.69 (3.80)	3.36 (4.16)	2.69 (3.80)	3.36 (4.16)						
	COP (Max.)		4.62 (4.33)	4.67 (4.25)	4.31 (4.28)	4.67 (4.25)	4.31 (4.28)						
7°C/55°C radiator*1	Heating capacity (Max.)	kW	8.24 (12.3)	9.16 (13.7)	10.09 (15.5)	9.16 (13.7)	10.09 (15.5)						
	Input power (Max.)		2.79 (4.15)	3.06 (4.72)	3.36 (5.41)	3.06 (4.72)	3.36 (5.41)						
	COP (Max.)		2.95 (2.96)	2.99 (2.91)	3.00 (2.87)	2.99 (2.91)	3.00 (2.87)						
-7°C/55°C radiator*1	Heating capacity (Max.)	kW	7.10 (9.1)	8.63 (10.2)	10.28 (10.5)	8.63 (10.2)	10.28 (10.5)						
	Input power (Max.)		3.30 (4.26)	4.03 (4.84)	4.74 (4.99)	4.03 (4.84)	4.74 (4.99)						
	COP (Max.)		2.15 (2.14)	2.14 (2.12)	2.17 (2.11)	2.14 (2.12)	2.17 (2.11)						
<b>Space heating characteristics*2</b>			°C		55	35	55	35	55	35	55	35	
Energy efficiency class			A++	A+++	A++	A+++	A++	A+++	A++	A+++	A++	A+++	
Rated heat output (P <sub>rated</sub> )			kW	8.2	8.5	9.8	10.1	11.4	11.7	9.8	10.1	11.4	11.7
Seasonal space heating energy efficiency (η <sub>s</sub> )			%	131	183	135	183	137	185	135	183	137	185
Annual energy consumption			kWh	5,060	3,771	5,879	4,476	6,717	5,132	5,879	4,476	6,717	5,132
Sound power level*3			Outdoor unit	dB(A)		56	56	58	56	56	58	58	
<b>Indoor unit specifications</b>													
Power source			Single phase, 230 V, 50 Hz			3-phase, ~400 V, 50 Hz							
Dimensions H × W × D			mm		1,780 × 598 × 624	1,780 × 598 × 624	1,780 × 598 × 624	1,780 × 598 × 624	1,780 × 598 × 624				
Weight (Net)			kg		135	135	135	135	135				
Water circulation			Min./Max.		L/min	10/42	10/42	10/42	10/42				
DHW tank volume			L		190	190	190	190	190				
Buffer tank capacity			L		16	16	16	16	16				
Expansion vessel capacity			L		12	12	12	12	12				
Water flow temperature range			Max.		°C	60	60	60	60				
Water pipe connection diameter			Flow/Return		mm	Ø19.05/Ø19.05	Ø19.05/Ø19.05	Ø19.05/Ø19.05	Ø19.05/Ø19.05				
Electrical heater capacity			Heating		kW	6.0	6.0	6.0	9.0				
			DHW		kW	1.2	1.2	1.2	1.2				
Declared load profile					L	L	L	L	L				
Efficiency η <sub>DHW</sub>					%	116	116	116	116				
Heating up time					h30min	h20min	h10min	h20min	h10min				
COP(EN16147)					-	2.90	2.90	2.90	2.90				
<b>Outdoor unit specifications</b>													
Power source			Single phase, 230 V, 50 Hz			3-phase, ~400 V, 50 Hz							
Current			Max.		A	19.5	22.0	25.0	8.8	9.8			
Water flow temperature range			Max.		°C	60	60	60	60	60			
Dimensions H × W × D			mm		1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480	1,008 × 1,080 × 480				
Weight (Net)			kg		96	96	102	96	102				
Refrigerant			Type (Global Warming Potential)		R32		R32	R32	R32				
Additional refrigerant charge			Charge		kg		1.40	1.40	1.63	1.40	1.63		
Connection pipe			Diameter		Liquid		mm		Ø6.35	Ø6.35	Ø6.35		
					Gas				Ø12.7	Ø12.7	Ø12.7		
			Length		Min./Max.		m		3/25	3/25	3/25		
			Length (Pre-charge)		m				15	15	15		
			Height difference		Max.		m		20	20	20		
Operating range			Heating		°C				-25 to 35	-25 to 35	-25 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalwv.com/global/support/downloads/search/](http://www.generalwv.com/global/support/downloads/search/)  
\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.

**Outdoor Unit:**  
Single phase: WOHG100MQL/WOHG121MQL/WOHG140MQL  
3-phase: WOHK121MQL/WOHK140MQL



**Split type**  
High power series (Wall-mounted type)

**Indoor unit:**  
**WSHG140DG**

**Outdoor unit:**  
**WOHG112LHT / WOHG140LCTA**  
**[3-phase] WOHK112LCTA / WOHK140LCTA / WOHK160LCTA**



**Specifications**

Model Name	Indoor unit	WSHG140DG	WSHG140DG	WSHG140DG	WSHG140DG	WSHG140DG
	Outdoor unit	WOHG112LHT	WOHG140LCTA	WOHK112LCTA	WOHK140LCTA	WOHK160LCTA
<b>Capacity range</b>		11	14	11	14	16
7°C/35°C floor heating *1	Heating capacity	10.80	13.50	10.80	13.50	15.17
	Input power	2.54	3.23	2.51	3.20	3.70
	COP	4.25	4.18	4.30	4.22	4.10
2°C/35°C floor heating *1	Heating capacity	10.77	12.00	10.77	13.00	13.50
	Input power	3.44	3.87	3.40	4.15	4.34
	COP	3.13	3.10	3.17	3.13	3.11
-7°C/35°C floor heating *1	Heating capacity	10.38	11.54	10.38	12.20	13.50
	Input power	4.32	5.08	4.28	5.13	5.40
	COP	2.40	2.27	2.43	2.38	2.50
-7°C/55°C Radiator *1	Heating capacity	7.57	9.20	9.27	10.10	11.00
	Input power	4.57	5.08	5.09	5.65	6.29
	COP	1.66	1.81	1.82	1.79	1.75

**Space heating characteristics\*2**

Temperature application	°C	55	35	55	35	55	35	55	35	55	35
Energy efficiency class		A+	A++	A+	A+	A+	A++	A+	A++	A+	A+
Rated heat output (P <sub>rated</sub> )	kW	9	11	11	13	9	11	11	13	13	14
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	112	151	113	148	112	154	117	150	117	149
Annual energy consumption	kWh	6,704	6,062	8,041	6,824	6,669	5,930	7,803	6,738	9,062	7,408
Sound power level	Indoor unit	46		46		46		46		46	
	Outdoor unit	68		69		69		68		71	

**Indoor unit specifications**

Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Dimensions H × W × D	800 × 450 × 457				800 × 450 × 457			
Weight (Net)	40				40			
Water circulation	Min./Max.	L/min	19.5/39.0	24.4/48.7	19.5/39.0	24.4/48.7	27.4/54.8	
Buffer tank capacity	L	16	16					
Expansion vessel capacity	L	8	8					
Water flow temperature range	Max.	°C	60					
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4				Ø25.4/Ø25.4	
Electrical heater capacity	heating	kW	-					

**Outdoor unit specifications**


Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Current	Max.	A	22.0	25.0	9.0	9.5	10.5	
Dimensions H × W × D	mm				1,290 × 900 × 330			
Weight (Net)	kg				92			
Refrigerant	Type (Global Warming Potential)	R410A (2,088)						
	Charge	kg	2.50					
Additional refrigerant charge		g/m	50					
	Diameter	Liquid	Ø9.52					
Connection pipe		Gas	Ø15.88					
	Length	Min./Max.	m					
	Length (Pre-charge)		m					
	Height difference	Max.	m					
Operating range	Heating	°C	-25 to 35					

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalww.com/global/support/downloads/search/](http://www.generalww.com/global/support/downloads/search/)


**Dimensions**

(Unit: mm)

**Indoor Unit:**  
WSHG140DG



**Outdoor Unit:**  
WGHG140DG



**Split type**  
High power series (DHW Integrated type)

**Indoor unit:**  
**WGHG140DG**

**Outdoor unit:**  
**WOHG112LHT / WOHG140LCTA**  
**[3-phase] WOHK112LCTA / WOHK140LCTA / WOHK160LCTA**



**Specifications**

Model Name	Indoor unit	WGHG140DG	WGHG140DG	WGHG140DG	WGHG140DG	WGHG140DG
	Outdoor unit	WOHG112LHT	WOHG140LCTA	WOHK112LCTA	WOHK140LCTA	WOHK160LCTA
<b>Capacity range</b>		11	14	11	14	16
7°C/35°C floor heating *1	Heating capacity	10.80	13.50	10.80	13.50	15.17
	Input power	2.54	3.23	2.51	3.20	3.70
	COP	4.25	4.18	4.30	4.22	4.10
2°C/35°C floor heating *1	Heating capacity	10.77	12.00	10.77	13.00	13.50
	Input power	3.44	3.87	3.40	4.15	4.34
	COP	3.13	3.10	3.17	3.13	3.11
-7°C/35°C floor heating *1	Heating capacity	10.38	11.54	10.38	12.20	13.50
	Input power	4.32	5.08	4.28	5.13	5.40
	COP	2.40	2.27	2.43	2.38	2.50
-7°C/55°C Radiator *1	Heating capacity	7.57	9.20	9.27	10.10	11.00
	Input power	4.57	5.08	5.09	5.65	6.29
	COP	1.66	1.81	1.82	1.79	1.75

**Space heating characteristics\*2**

Temperature application	°C	55	35	55	35	55	35	55	35	55	35
Energy efficiency class		A+	A++	A+	A+	A+	A++	A+	A++	A+	A+
Rated heat output (P <sub>rated</sub> )	kW	9	11	11	13	9	11	11	13	13	14
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	112	151	113	148	112	154	117	150	117	149
Annual energy consumption	kWh	6,704	6,062	8,041	6,824	6,669	5,930	7,803	6,738	9,062	7,408
Sound power level	Indoor unit	46		46		46		46		46	
	Outdoor unit	68		69		69		68		71	

**Domestic hot water characteristics\*2**

Load profile	L										
Energy efficiency class	A										
Energy efficiency (η <sub>dw</sub> )	88										
Annual electricity consumption	kWh										

**Indoor unit specifications**


Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Dimensions H × W × D	mm				1,840 × 648 × 698			
Weight (Net)	kg				150			
Water circulation	Min./Max.	L/min	19.5/39.0	24.4/28.7	19.5/39.0	24.4/48.7	27.4/54.8	
DHW tank volume	L	190						
Electrical heater capacity	Heating	kW						
	DHW	kW						
Buffer tank capacity	L	1.5						
Expansion vessel capacity	L	16						
Water flow temperature range	Max.	°C						
Water pipe connection diameter	Flow/Return	mm						
Hot water pipe connection diameter		mm						

**Outdoor unit specifications**


Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Current	Max.	A	22.0	25.0	9.0	9.5	10.5	
Dimensions H × W × D	mm				1,290 × 900 × 330			
Weight (Net)	kg				92			
Refrigerant	Type (Global Warming Potential)	R410A (2,088)						
	Charge	kg	2.50					
Additional refrigerant charge		g/m	50					
	Diameter	Liquid	mm					
Connection pipe		Gas	mm					
	Length	Min./Max.	m					
	Length (Pre-charge)		m					
	Height difference	Max.	m					
Operating range	Heating	°C	-25 to 35					

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.generalww.com/global/support/downloads/search/](http://www.generalww.com/global/support/downloads/search/)

**Outdoor Unit:**  
Single phase: WOHG112LHT/WOHG140LCTA




3-phase: WOHK112LCTA/WOHK140LCTA/WOHK160LCTA



**Split type**  
Super high power series (Wall-mounted type)

**Indoor unit:**  
**WSHG160DJ6**  
**Outdoor unit:**  
**WOHG160LJL**



**Specifications**

Model Name	Indoor unit	Outdoor unit	WSHG160DJ6	WOHG160LJL	
<b>Capacity range</b>					
7°C/35°C floor heating *1	Heating capacity	kW	16.00		
	Input power		3.86		
	COP		4.15		
2°C/35°C floor heating *1	Heating capacity	kW	13.30		
	Input power		4.25		
	COP		3.13		
-7°C/35°C floor heating*1	Heating capacity	kW	14.50		
	Input power		5.27		
	COP		2.75		
-7°C/55°C Radiator*1	Heating capacity	kW	10.90		
	Input power		5.89		
	COP		1.85		
<b>Space heating characteristics*2</b>					
Temperature application	°C		55	35	
Energy efficiency class			A++	A++	
Rated heat output (P <sub>rated</sub> )	kW		14	16	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%		125	163	
Annual energy consumption	kWh		8,757	8,014	
Sound power level	Indoor unit	dB(A)	45	45	
	Outdoor unit		67	66	
<b>Indoor unit specifications</b>					
Power source	Single phase, ~230 V, 50 Hz				
Dimensions H × W × D	mm	805 × 450 × 471			
Weight (Net)	kg	52.5			
Water circulation	Min./Max.	L/min	26.4/57.8		
Buffer tank capacity	L	22			
Expansion vessel capacity	L	10			
Water flow temperature range	Max.	°C	60		
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4		
Electrical heater capacity	Heating	kW	6.0 (3.0 kW × 2 pcs.)		
<b>Outdoor unit specifications</b>					
Power source	Single phase, ~230 V, 50 Hz				
Current	Max.	A	28.0		
Dimensions H × W × D	mm	1,428 × 1,080 × 480			
Weight (Net)	kg	137			
Refrigerant	Type (Global Warming Potential)	R410A (2,088)			
Additional refrigerant charge	Charge	kg	3.80		
		g/m	50		
Connection pipe	Diameter	Liquid	mm	Ø9.52	
		Gas	mm	Ø15.88	
	Length	Min./Max.	m	5/30	
		Length (Pre-charge)	m	15	
Height difference	Max.	m	25/15 (Outdoor unit: Upper/Lower)		
	Heating	°C	-25 to 35		


\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.

\*2: Information about ErP can be downloaded from our website at [www.generalww.com/global/support/downloads/search/](http://www.generalww.com/global/support/downloads/search/)


**Dimensions**

(Unit: mm)

**Indoor Unit:**  
WSHG160DJ6




**Outdoor Unit:**  
WOHG160LJL



**Split type**  
Super high power series (DHW Integrated type)

**Indoor unit:**  
**WGHG160DJ6**  
**Outdoor unit:**  
**WOHG160LJL**




**Specifications**

Model Name	Indoor unit	Outdoor unit	WGHG160DJ6	WOHG160LJL	
<b>Capacity range</b>					
7°C/35°C floor heating *1	Heating capacity	kW	16.00		
	Input power		3.86		
	COP		4.15		
2°C/35°C floor heating *1	Heating capacity	kW	13.30		
	Input power		4.25		
	COP		3.13		
-7°C/35°C floor heating*1	Heating capacity	kW	14.50		
	Input power		5.27		
	COP		2.75		
-7°C/55°C Radiator*1	Heating capacity	kW	10.90		
	Input power		5.89		
	COP		1.85		
<b>Space heating characteristics*2</b>					
Temperature application	°C		55	35	
Energy efficiency class			A++	A++	
Rated heat output (P <sub>rated</sub> )	kW		14	16	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%		125	163	
Annual energy consumption	kWh		8,757	8,014	
Sound power level	Indoor unit	dB(A)	45	45	
	Outdoor unit		67	66	
<b>Domestic hot water characteristics*2</b>					
Load profile	L				
Energy efficiency class	A				
Energy efficiency (η <sub>DHW</sub> )	%	109			
Annual electricity consumption	kWh	941			
<b>Indoor unit specifications</b>					
Power source	Single phase, ~230 V, 50 Hz				
Dimensions H × W × D	mm	1,841 × 648 × 698			
Weight (Net)	kg	166			
Water circulation	Min./Max.	L/min	26.4/57.8		
DHW tank volume	L	190			
Electrical heater capacity	Heating	kW	6.0 (3.0 kW × 2 pcs.)		
	DHW		1.5		
Buffer tank capacity	L	22			
Expansion vessel capacity	L	12			
Water flow temperature range	Max.	°C	60		
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4		
Hot water pipe connection diameter	mm	Ø19.05			
<b>Outdoor unit specifications</b>					
Power source	Single phase, ~230 V, 50 Hz				
Current	Max.	A	28.0		
Dimensions H × W × D	mm	1,428 × 1,080 × 480			
Weight (Net)	kg	137			
Refrigerant	Type (Global Warming Potential)	R410A (2,088)			
Additional refrigerant charge	Charge	kg	3.80		
		g/m	50		
Connection pipe	Diameter	Liquid	mm	Ø9.52	
		Gas	mm	Ø15.88	
	Length	Min./Max.	m	5/30	
		Length (Pre-charge)	m	15	
Height difference	Max.	m	25/15 (Outdoor unit: Upper/Lower)		
	Heating	°C	-25 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.

\*2: Information about ErP can be downloaded from our website at [www.generalww.com/global/support/downloads/search/](http://www.generalww.com/global/support/downloads/search/)

**Outdoor Unit:**  
WOHG160LJL





# Indoor Unit

Type-A  
Type-B

## Selecting the indoor unit

- This is a device for storing hot water and circulating it to housing equipment.
- Selection criteria for the indoor unit is which housing equipment it will be connected to, such as a radiator or shower.
- Indoor unit you choose will also depend on whether you already own devices such as a pump or tank.



Radiator, Fan coil



Shower, Bath



Under floor heating

Domestic hot water



## What Each Indoor Unit Can Do



### Indoor unit control box\*

If you want to update your system by reusing your existing pump and buffer tank, etc., you can do so by installing only the control box.



### Indoor unit Wall-mounted

Stands for preparation of heating water for under floor heating and radiators. It can optionally operate with domestic hot water tank.



### Indoor unit Domestic Hot Water (DHW) integrated

Can be used with a variety of heating systems, including under floor heating and radiators. Space saving heating and DHW supply in a single indoor unit.

\*The control box can only be selected for Monobloc outdoor unit.

## Types of Indoor Units



Compatibility for Monobloc type Comfort series / Split type High power series\*

\*The R32 High Power Series cannot be connected to the control box.



Indoor unit type	Control box*	Wall-mounted	DHW integrated
<b>Housing Equipment</b>			
Under floor heating	○	●	●
Radiator	○	●	●
Fan coil	○	●	●
Bath	○	○	●
Shower	○	○	●
Hot Water	○	○	●



Compatibility for Split type Comfort series, High power series Super high power series



Indoor unit type	Wall-mounted	DHW integrated
<b>Housing Equipment</b>		
Under floor heating	●	●
Radiator	●	●
Fan coil	●	●
Bath	○	●
Shower	○	●
Hot water	○	●

● : It can be used by constructing a system using options and carrying out water pipe work.  
○ : It can be used by constructing a system using options and carrying out water pipe work, by reusing (or locally procuring) existing pumps and tanks, etc.  
Housing Equipment requires the preparation of separately sold products.

Type-A


# Comfort Control

## Useful Features

Flow temperature control with climate compensation


### Automatic Heating Curve Control

Automatic temperature regulation according to heating curve (depending on heating terminal and outdoor temperature)



### Auto Changeover

When Auto mode is selected, the system automatically switches between cooling and heating modes depending on the outdoor temperature to serve as an all-season air conditioner.




### Quick Recovery from Defrosting

Maintains room temperature by boost start operation during defrosting.

### 2-zone Independent Control

2-zone independent control (For example, the individual control of 2 underfloor heating zones or the combination of 1 underfloor heating zone and 1 radiator zone)\*\*2



\*1: Optional parts such as 2-zone kits, 3-zone kits, and thermostats are required  
\*2: 3 Zones can be controlled in the Control Box

### Backup Heater Operation

Backup heater maintains a comfortable room temperature even when the outside temperature is low. The backup heater is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.

## Controller with a clear color display and simple icons for easy function settings

#### Color display

Shows all the information items related to the operation mode:  
WLAN Connectivity / Operation / Pressure / Set temperature (DHW/Flow) Clock / Message / Service maintenance



Operation indicator  
Fixed white: Normal operation  
Flashing orange: Error

Menu access button

Navigation knob:  
Rotation: Menu navigation  
Press: Validation

Back button

### Main operation flow and settings for installers and end users

	Flow Chart	Example Item
Installers	1 Install Settings	Pump speed setting, Configuration, Heating curve setting, Heat pump shut off
	2 Option Settings	Cooling Kit, DHW Kit, Boiler Kit
	3 Convenient Function	Automatic heating curve settings, Underfloor controlled driving, Outdoor temperature adjustment, Maintenance period settings
	4 Workout Settings	Outdoor temperature simulator
	5 Confirmation	Checking operation (Heating and cooling, DHW, option)
End users	6 User Settings	Date and time, Time program, Operation temperature settings

## Energy Saving

### Away mode

It will set heating and DHW mode to the frost protection\* during the selected period:

-If you activate away mode on HMI: You can choose start and end time/date.

-If you activate away mode on Room thermostat (option): You can choose start and end time/date, as well as room setpoint during away period.

\*: The protection mode automatically prevents an excessively sharp drop in room temperature.

## Safety Features

### Anti-freeze function\*

When the outside temperature drops below a specified level, the outdoor unit water pump will self-activate and water will also be automatically circulated to prevent freezing.

\*The R32 High Power Series is excluded.

## Easy Installation & Maintenance

- All hydraulic safety and control components are built in with no additional selection required.
- Easy access for maintenance
- Refrigerant pump down operation

### Error and Maintenance Alarm

Enables quick error-handling services and maintenance

✘ Error ⚠ Warning



### Maintenance Support


Diagnostics functions for troubleshooting



### Easy to Set Up

#### Easy Start

Choose language, set date and time. Answer questions from Easy Start.



### Remote Connectivity and Control

Via app "Cozy touch", you can manage and control of electric heaters, electric water heaters, heat pump water heaters, heat pumps.


\* Cozytouch is a service of Group Atlantic



Type-A

# Optional Parts & Control Overview

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.



## for Indoor unit



**Electrical backup heater relay**  
UTW-KBHXQ  
It allows the backup heater for heating at 3 kW as standard can be used at 6 kW.

## for Outdoor unit



**Drain pan**  
UTW-KDPXQ  
It is used to collect and drain condensation water generated by outdoor unit.



**Antivibration Rubber feet**  
UTW-KARXQ  
It reduces vibration caused by the operation of compressors and other equipment, and suppresses the generation of noise.




**Antifreezing valve for Monobloc**  
UTW-KAVXQ  
When water pipes freeze, the internal pressure increases and the pipes are purged to prevent parts from breaking.

## for Locally units




**Second Circuit Kit**  
It can supply hot water at different temperatures to each two types of heating equipment, such as radiators and underfloor heating.

UTW-KZSXQ



UTW-KZC2XQ



UTW-KZDXQ



UTW-KBCXQ

**Boiler Connection Kit**

It can build hybrid systems using both boilers and heat pumps. Boiler and heat pumps are switched according to outside air temperature.



## for DHW



**DHW Kit**  
Required to connect locally purchased DHW tanks to Air to Water.

UTW-KDWXQ

UTW-KDWCXQ



**DHW tank**  
200 Liters: UTW-T20AXH / UTW-T20BXH  
300 Liters: UTW-T30AXH / UTW-T30BXH  
The BXH series is a more efficient tank than the AXH series.



**DHW Expansion Kit**  
UTW-KDEXQ  
The expansion vessel(18L) for connection to DHW water pipe.

## Service & Maintenance Tool

**Service Monitor Tool**  
UTY-ASSXZ1



Indoor unit Controller

DHW Integrated

Monobloc type Comfort series

## Individual Control

**Room thermostat**  
An optional wireless thermostat allows remote control of the ATW system away from the indoor unit. Can also be operated from mobile apps.



Wired power supply  
UTW-C225XQ
































Battery power supply  
UTW-C228XQ

**Cozy tough (Application)**  
\* Cozytouch is a service of Group Atlantic



# Type-A Optional Parts List

Product Name	Model Name	Monobloc Type				Split Type		
		Comfort series				High Power Series		
		1Ø				1Ø/3Ø		
		Controll Box	Wall-mounted	DHW integrated	Outdoor Unit	Wall-mounted	DHW integrated	Outdoor Unit
Second Circuit Kit 	UTW-KZSXQ		•*			•*		
DHW Kit 	UTW-KDWXQ		•			•		
Boiler Kit 	UTW-KBSXS					•		
Boiler Connection Kit 	UTW-KBDXS					•		
Second Circuit Kit 	UTW-KZDXQ			•*		•*		
DHW Loop Kit 	UTW-KDLXQ			•		•		
DHW Expansion Kit 	UTW-KDEXQ			•		•		
Outdoor temperature sensor 	UTW-KESXQ	•	•	•		•	•	
Condensation detection kit 	UTW-KCDXQ	•	•	•		•	•	
Regulation Extension Kit 	UTW-KREXQ	•	•	•		•	•	
Electrical Backup heater relay 	UTW-KBHXQ		•	•				
Room thermostat (Wired)  <small>Wired power supply</small>	UTW-C105XQ	•	•	•		•	•	
Room thermostat (Wireless) 	UTW-C225XQ	•	•	•		•	•	
	UTW-C228XQ	•	•	•		•	•	
Cover Plate for thermostat 	UTW-KCPXQ	•	•	•		•	•	
Dual circuit decoupling kit 	UTW-KZVXS					•	•	

Product Name	Model Name	Monobloc Type				Split Type		
		Comfort series				High Power Series		
		1Ø				1Ø/3Ø		
		Controll Box	Wall-mounted	DHW integrated	Outdoor Unit	Wall-mounted	DHW integrated	Outdoor Unit
Flow kit 	UTW-PHFXS					•	•	
High flow kit 	UTW-PHFXS					•	•	
Drain pan 	UTW-KDPXQ					•	•	
Antivibration Rubber feet 	UTW-KARXQ					•	•	
Antifreezing valve for Monobloc 	UTW-KAVXQ					•		
Single Circuit Kit  (x1)	UTW-KZC1XQ	•						
Second Circuit Kit  (x2)	UTW-KZC2XQ	•						
		 (x1)	•					
Third Circuit Kit  (x2)	UTW-KZC3XQ	•						
		 (x1)	•					
Boiler Connection Kit 	UTW-KBCXQ	•						
DHW Kit 	UTW-KDWCXQ	•						
Backup Heater Kit 	UTW-HB6CXQ	•						
DHW tank 	UTW-T20AXH UTW-T30AXH	•	•			•		
	UTW-T20BXH UTW-T30BXH	•	•			•		

\*1: Regulation extension kit (UTW-KREXQ) is not included but is required for connection.

Type-**B**

# Comfort Control

The high-grade heating controller automatically adjusts the flow temperature according to the climate conditions to maintain the room and domestic hot water temperatures at the desired levels.

### Indoor unit Controller

#### 4 Heating modes

##### 1. Automatic mode

Enables automatic switching between Comfort mode and Reduce mode according to time program

##### 2. Reduce mode

Maintains water temperature at a lower level

##### 3. Comfort mode

Maintains water temperature at a comfortable level

##### 4. Protection mode


Activates frost protection in standby operation



## Useful Features


### Automatic Heating Curve Control

Automatic temperature regulation according to heating curve (depending on heating terminal and outdoor temperature)



The heating curve will shift to adjust the room temperature setting.

Can be fine-adjusted when it is too warm or too cold.



### Quick Recovery from Defrosting

Maintains room temperature by boost start operation during defrosting.


### Auto Changeover

When cooling mode is selected, the system automatically switches between cooling and heating modes depending on the outdoor temperature to serve as an all-season air conditioner.

### 2-Zone Independent Control

2-zone independent control (For example, the individual control of 2 underfloor heating zones or the combination of 1 underfloor heating zone and 1 radiator zone)<sup>\*1</sup>


\*1: Optional parts required



### 2-Stage Low-Noise Mode

The outdoor unit can be switched to quiet mode, depending on the installation environment.

\*Effective only for high power series



### Backup Heater Operation

Backup heater maintains a comfortable room temperature even when the outside temperature is low. The backup heater is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.

\* Optional parts is needed for high power series.

## Energy Saving

### Time Program

- The timer is easy to set.
- You can select the heating mode in conjunction with various times of the day.

#### Day-weekly timer

- Allows up to 3 settings per day.
- Allows individual settings for each day of the week.

#### Holiday timer

- Allows up to 8 settings.
- While you are away from home for an extended period during winter, the system prevents your room or house from freezing.

### Peak Cut Function\*2

Sets the peak current value to reduce power consumption.


Mode	Ratio to reduce power consumption
1	100%
2	75%
3	50%
4	Almost 0%

\* Please refer to page W-054 and W-055 for optional parts information.

## Safety Features


### Anti-Legionella Function

Prevents the growth of Legionella bacteria in the DHW tank to supply safe and clean hot water at all times.




### Anti-Freeze Function

When the outside temperature drops below a specified level, the compressor will self-activate and water will also be automatically circulated to prevent freezing.



### Emergency Operation

If an outdoor unit fails to operate, a built-in backup heater or an external boiler is activated to supply an uninterrupted supply of hot water to the house.




### Error and Maintenance Alarm

Enables quick error-handling services and maintenance



- Error history saves 10 errors in memory
- Display telephone number of service company




Type-**B**

# Simple Installation

## Presetting Configurations

A controller installed makes it easy to configure the system without having to set each component or unit individually.




8 simple patterns for system presetting (Pair of heating: 12 patterns)

Configuration (Parameter 5700)	Installation type
Presetting 1	1 heating circuit
Presetting 2	2 heating circuits
Presetting 3	1 heating circuit with boiler backup
Presetting 4	2 heating circuits with boiler backup
Presetting 5	1/2 heating circuit with buffer control
Presetting 6	1/2 heating circuit with buffer control and boiler backup
Presetting 7	Cascade connection Primary
Presetting 8	Cascade connection A
Presetting 9	Cascade connection B/C

- DHW & solar control auto detection
- Cascade connection only available in High Power models.

## Outdoor Temperature Simulation


It verifies that each unit operates properly under the set conditions and expected outdoor air temperature when the system is actually assembled.




The outdoor temperatures can be simulated in the range of -50°C to +50°C.

## Concrete Floor Drying

Allows the concrete surrounding the hot-water pipes to dry more quickly, shortening the construction period for underfloor heating installations.



## Controller with a large liquid crystal display and buttons for easy function settings



### Main operation flow and settings for installers and end users


	Flow Chart	Example Item
Installers	1 Install Settings	Pump speed setting, Configuration, Heating curve setting, Heat pump shut off
	2 Option Settings	Cooling Kit, DHW Kit, Boiler Kit
	3 Convenien Function	Automatic heating curve settings, Underfloor controlled driving, Outdoor temperature adjustment, Maintenance period settings
	4 Workout Settings	Outdoor temperature simulator
	5 Confirmation	Checking operation (Heating and cooling, DHW, option)
End users	6 User Settings	Date and time, Time program, Operation temperature settings

# Easy Installation & Maintenance

- All hydraulic safety and control components are built in with no additional selection required.
- Lifting bars for installation free of difficulty or risk
- Easy access for maintenance
- Refrigerant pump down operation

## Maintenance Support


### Diagnostics functions for troubleshooting



Type-**B**

# Control Overview

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.



Type-**B**

# Optional Parts Overview

Various optional parts are available to use ATW according to needs and environments.



## for Locally units



### Second Circuit Kit

It can supply hot water at different temperatures to each two types of heating equipment, such as radiators and underfloor heating.

UTW-KZSXE\*1



UTW-KZDXE\*1



UTW-KZSXJ



UTW-KZDXJ

### Boiler Connection Kit

It can build hybrid systems using both boilers and heat pumps. Boiler and heat pumps are switched according to outside air temperature.



UTW-KBSXD



UTW-KBDXD



UTW-KBSXJ

\*1: The UTW-KREXD (Regulation Extension Kit) is not included but is required for connection.



## for Indoor unit



### Circulating Pump

UTW-PHFYG

The high-output pump for replacement of the standard pump in the hydraulic unit. It can be used in properties with longer and more complex water pipe.

### Cascade Master/Slave Kit

Up to 3 indoor units can be connected for large-capacity use. It is need to install a primary kit in one unit and a secondary kit in one or two other units.



Cascade Master Kit (incl. LPB clip)



Cascade Slave Kit (incl. LPB clip)

### Cooling Kit

Required when using ATW also for cooling operation. It is used to prevent condensation occurring in the indoor unit.



UTW-KCLXD



UTW-KCLXL

## for Outdoor unit



### Drain Pan

UTW-KDPXB

It is used to collect and drain condensation water generated by outdoor unit.



### External Connection Kit

UTY-XWZXZ2 / UTY-XWZXZ3

The signal input (low noise mode, peak cut) and signal output (compressor operation, base pan heater control) for outdoor unit are possible externally.

## for DHW



### DHW Kit

UTW-KDWXD (External)

Required to connect locally purchased DHW tanks to Air to Water.




### DHW Tank

200 Liters: UTW-T20AXH / UTW-T20BXH

300 Liters: UTW-T30AXH / UTW-T30BXH

The BXH series is a more efficient tank than the AXH series.



UTW-KDEXE



UTW-KDEXL

### DHW Expansion Kit

The expansion vessel(18L) for connection to DHW water pipe.



# Type-B Optional Parts List

Product Name	Model Name	Split Type										Split DHW Integrated Type									
		Super High Power		High Power				R32 Comfort				Super High Power		High Power				R32 Comfort			
		1Ø	16	1Ø		3Ø		1Ø				1Ø	16	1Ø		3Ø		1Ø			
		11	14	11	14	16	5	6	8	10	16	11	14	11	14	16	5	6	8	10	
Second Circuit Kit	UTW-KZSXE	-	•*	•*	•*	•*	•*	•*	•*	•*	-	-	-	-	-	-	-	-	-	-	
	UTW-KZDXE	-	-	-	-	-	-	-	-	-	-	•*	•*	•*	•*	•*	•*	•*	•*	•*	
	UTW-KZSXJ	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	UTW-KZDXJ	-	-	-	-	-	-	-	-	-	•	-	-	-	-	-	-	-	-	-	
Boiler Connection Kit	UTW-KBSXD	-	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	
	UTW-KBDXD	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	•	•	•	•	
	UTW-KBSXJ	•	-	-	-	-	-	-	-	-	•	-	-	-	-	-	-	-	-	-	
Balancing vessel	UTW-TEVXA	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
DHW Kit	UTW-KDWXD (External)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
DHW tank	200 Liters 300 Liters UTW-T20AXH UTW-T30AXH	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	200 Liters 300 Liters UTW-T20BXH UTW-T30BXH	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
DHW Expansion Kit	UTW-KDEXE	-	-	-	-	-	-	-	-	-	•	•	•	•	•	-	-	-	-	-	
	UTW-KDEXL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	
Circulating pump	UTW-PHFXG	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	
Cooling Kit	UTW-KCLXD	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	
	UTW-KCLXL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	
Regulation Extension Kit	UTW-KREXD	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Drain pan	UTW-KDPXB	-	-	-	-	-	•	•	•	-	-	-	-	-	•	•	•	-	-	-	
Cascade Master Kit (incl. LPB clip)	UTW-KCMXE	-	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	
Cascade Slave Kit (incl. LPB clip)	UTW-KCSXE	-	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	

Product Name	Model Name	Split Type										Split DHW Integrated Type									
		Super High Power		High Power				R32 Comfort				Super High Power		High Power				R32 Comfort			
		1Ø	16	1Ø		3Ø		1Ø				1Ø	16	1Ø		3Ø		1Ø			
		11	14	11	14	16	5	6	8	10	16	11	14	11	14	16	5	6	8	10	
HMI Kit	UTW-KHMXE	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
Remote controller	Wired UTW-C74TXF	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
	UTW-C74HXF	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
Room thermostat	Wired UTW-C55XA	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	Wireless UTW-C58XD	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
Outdoor sensor transmitter	UTW-MOSXD	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
RF modules for BSB-Port	UTW-MRCXD	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Web server	UTW-KW1XD	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
	UTW-KW4XD	-	•*	•*	•*	•*	•*	-	-	-	-	-	-	-	-	-	-	-	-	-	
LPB clip	UTW-KL1XD	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
MODBUS® clip	UTW-KMBXJ	-	•*	•*	•*	•*	•*	-	-	-	-	-	-	-	•*	•*	•*	•*	•*		
Service tool (incl. OCI700 Adapter)	UTW-KSTXD	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
Service tool software	UTW-KPSXD	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	•*	
External Connect Kit	UTY-XWZXZ2	-	•	•	•	•	•	-	-	-	-	-	-	-	•	•	•	•	•		
	UTY-XWZXZ3	•	-	-	-	-	-	-	-	-	•	•	•	•	•	-	-	-	-	•	
Back-up Heater	UTW-HS6XG	-	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	UTW-HT9XG	-	-	-	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	
Electrical backup heater relay	UTW-KBHXL	-	-	-	-	-	•	•	•	•	-	-	-	-	•	•	•	•	•		

\*1: The UTW-KREXD (Regulation Extension Kit) is not included but is required for connection.  
 \*2: Split DHW integrated type supplies DHW without the DHW Kit and DHW tank.  
 \*3: Includes 21 languages with no need to prepare an RC for Eastern Europe separately.  
 \*4: UTW-MRCXD (RF modules) is required for the connection.  
 \*5: The connection of UTW-KW4XD for simultaneous control of multiple ATW units is only possible for cascade systems.  
 \*6: Additional Spare parts 9708302034 (Analogue interface PCB) and 109696 (connection wire) are required.  
 \*7: UTW-KL1XD (LPB clip) is required for the connection.  
 \*8: UTW-KW1XD or UTW-KW4XD (Web server) is required for the connection.

•: Available    -: Not Available